

Broan Ventilation Fans—High Capacity

200/250/300 CFM High Capacity Fan Features

- 8" round duct connector
- Single, impact-resistant centrifugal blower wheel (Model L300KMG has a metal wheel)
- 20 gauge galvanized steel housing
- Duct horizontally or vertically
- In-line ducting available with separate adapter
- Ceiling mount models available in 240V (add EX to model number) and 277V (add C to model number)
- Models L200L, L250L and L300L are UL Listed for use over bathtubs or showers when connected to a GFCI branch circuit
- Use Broan Electronic Variable Speed Control to adjust blower speed and sound level (available separately)

Polymeric Grille



Model L200 (shown)


- 120V, 1.8 amps

Model L250

- 120V, 2.1 amps

Model L300

- 120V, 2.6 amps



Metal Grille



Model L200MG (shown)

- 120V, 1.8 amps

Model L250MG


- 120V, 2.1 amps

Model L300MG


- 120V, 2.6 amps

Model L300KMG

- Suitable for kitchen installations
- 120V, 2.6 amps
- Metal wheel
- Order Aluminum Filter LAF1



In-Line Ventilators



- Suitable for kitchen installations

- Removable access panel – no insulation

Model L200L (shown)

- 120V, 1.8 amps

Model L250L

- 120V, 2.1 amps

Model L300L

- 120V, 2.6 amps

Model	CFM	Sones	Notes
L200	210	1.7	White polymeric grille
L200MG	215	1.9	White Metal grille
L200L	195	1.9	In-line
L250	259	2.2	White polymeric grille
L250MG	265	2.5	White Metal grille
L250L	245	2.3	In-line
L300	308	2.9	White polymeric grille
L300MG	316	3.0	White Metal grille
L300L	293	3.1	In-line
L300KMG	277	3.1	White Metal grille

Sones and CFM listed for ceiling mount models are for horizontal ducting at .125" static pressure. For in-line models, performance listed is for straight-thru ducting at .125" static pressure. For complete Sones and CFM at other static pressures, see our web site at www.Broan.com.



Adjust ventilation easily in any room.

Model 80L Variable Speed Control mounts inside the fan housing and allows blower speed adjustment to balance ventilation.

- For Broan High Capacity Fans L100-L900L
- Speed control with metal housing
- Fan insulation is performed for easy installation
- 120 V, 3 amps, 60 Hz
- UL Listed

